

Environmental Test Chambers

ISUZU

EPR-114 Oven

Features:

- Hot Air Circulation Method
- JIS K-Type, Thermo Couple Temperature Sensor
- Sheathed Heater (SUS-304)
- 2 Shelf Racks (Up to 15 kg/rack)
- Top Exhaust Outlet Port (Diameter: 35 mm)
- Left Side Cable Access Port (Diameter: 35 mm)
- RS-485 Communication Option



[Click here to convert specifications to US](#)

| Model | EPR-114 |
|----------------------------|--|
| Temperature Range | 40 to 260 °C |
| Time to Reach Max. Temp. | 50 min. |
| Temp Distribution Accuracy | +/- 1.5 °C at 100 °C +/- 2.5 °C at 200 °C +/- 3.0 °C at 260 °C |
| Heater Wattage | 1.4 KW |
| Inside Cubic Volume | 91 L |
| Inside Dimensions | 450W x 450D x 450H mm |
| Outside Dimensions | 750W x 636D x 906H mm |
| Observation Window | 200W x 400H mm |
| Interior Construction | Stainless Steel SUS-304 |
| Weight | 57 kg |
| Power Supply Voltage | AC 100V – Single Phase |
| Max. Power Consumption | 1.2 KVA |

Factory Sales and Technical Support Center

Hastest Solutions Inc., 4423 Fortran Drive, Building 190, San Jose, CA
95134, USA

Tel: 408 945 7861 Fax: 408 262 6699