

Environmental Test Chambers

ISUZU

EPR-115 Oven

Features:

- Hot Air Circulation Method
- JIS K-Type, Thermo Couple Temperature Sensor
- Sheathed Heater (SUS-304)
- 2 Shelf Racks (Up to 15 kg/rack)
- Top Exhaust Outlet Port (Diameter: 35 mm)
- Left Side Cable Access Port (Diameter: 35 mm)
- RS-485 Communication Option



[Click here to convert specifications to US](#)

Model	EPR-115
Temperature Range	40 to 260 °C
Time to Reach Max. Temp.	50 min.
Temp Distribution Accuracy	+/- 1.5 °C at 100 °C +/- 2.5 °C at 200 °C +/- 3.0 °C at 260 °C
Heater Wattage	1.4 KW
Inside Cubic Volume	150 L
Inside Dimensions	600W x 500D x 500H mm
Outside Dimensions	750W x 636D x 906H mm
Observation Window	200W x 400H mm
Interior Construction	Stainless Steel SUS-304
Weight	57 kg
Power Supply Voltage	AC 100V – Single Phase
Max. Power Consumption	1.2 KVA

Factory Sales and Technical Support Center

Hastest Solutions Inc., 4423 Fortran Drive, Building 190, San Jose, CA
95134, USA

Tel: 408 945 7861 Fax: 408 262 6699