

HAST Products

HIRAYAMA

PC - R8 series "HAST" Chambers (Unsaturated/Saturated type HAST/PCT) Highly Accelerated Stress Test

Features:

- Bright and easy-to-see LCD.
- Easier Operation with Touch-Screen Input.
- High Precision System with Test Chamber and separate Steam Generator.
- New System of Electric Clamping Door with Sliding Tray.
- Various Convenient Functions such as Graphic Display, Test Title Registration, Alarm Messages, etc.
- Dual Operation Modes with 3 Exhaust Systems.
- Up to 60 BIAS Terminals & Automatic.
- Water Feeding as Optional Features.



[Click here to convert specifications to US](#)

Model	PC-422R8
Outer Dimensions	710W x 555D x 1560H mm
Test Chamber Size	420 ø x 555D mm
Test Chamber Volume	76.2 l
Effective Chamber Size	340 ø x 475D mm
Effective Chamber Volume	38.2 l
Usable Pressure Range	0.019 ~ 0.208 Mpa
Power Source	AC220/230/240V, single-phase, 3.2kW
Usable Temperature / Humidity Range	105.0 ~ 150.0 °C (100 ~ 65% RH)

Meets the requirements of JEDEC-110B, JIS-C0096, IEC 60068-2-66 and other test conditions.